



Encl., NewVegaD, 1287x550x150mm, 168 mod.

FU72DN

#### Architecture

Fixing mode	flush-mounting
-------------	----------------

#### Configuration

Module	with terminals
--------	----------------

#### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

#### Electric current

Rated current	160 A
---------------	-------

#### Cover, door

Cover type	With Notch
Door locking	without
Door leave	single
Cover type	none / closed
Transparent cover or door	no

#### Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Type of surface treatment	powder-coated

#### Dimensions

Insertion depth	110 mm
Depth of installed product	150 mm
Internal depth	110 mm
Height of installed product	1287 mm
Installation height	1287 mm
Width of installed product	600 mm
Width in division units	24
Thickness of sidewall material	1 mm
Built-in width	550 mm

#### Installation, mounting

Suitable for outdoor use	no
--------------------------	----

#### Connection

Number of conduit inlets	4
--------------------------	---

#### Accessories included

Mounting plate included	no
With lock	no

#### Equipment

Number of rows	7
Quantity of section in width	2
Quantity of rails	7
Can be accessorized	yes
Number of openings for flange plates	2
Extension possible	no

#### Standards

European directive WEEE	not concerned
-------------------------	---------------

#### Safety

IK protection code against mechanical impacts	IK07
Protection index IP	IP30
Protection class	isol.class II