



Sm.distr, golf, flush, MM, 72M, wh Door

Similar image
(Picture shows VF218PZD)

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

With a pipe-in lead	yes
---------------------	-----

Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

Cover, door

Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	With Notch
Door locking	without
Door leave	single
Door material	Plastic
Door quantity	1
Door transparent material	Plastic
Cover type	Door
Transparent cover or door	no

Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

Dimensions

Insertion depth	72 mm
Depth of wall niche	72 mm
Depth of installed product	97,5 mm
Internal depth	97,5 mm
Height of installed product	688 mm
Installation height	652 mm

Technical Properties

Width of installed product	460 mm
Width in division units	18
Thickness of sidewall material	3 mm
Built-in width	426 mm

Installation, mounting

Suitable for outdoor use	no
--------------------------	----

Accessories included

Mounting plate included	yes
With lock	no

Equipment

Number of units	18
Number of rows	4
Quantity of rails	4
Can be accessorized	yes
Extension possible	yes

Standards

GWT Glow wire test	650 °C
--------------------	--------

Safety

IK protection code against mechanical impacts	IK07
---	------