



Sm.distr, golf, flush, MM, 36M, wh door

VF218PZE

Architecture

Fixing mode	flush-mounting
-------------	----------------

Compatibility

Suitable for lightning protection	no
-----------------------------------	----

Cover, door

Material thickness cover	3 mm
Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	With Notch
Door leave	single
Door material	Plastic
Door quantity	1
Door transparent material	Plastic
Cover type	Door
Transparent cover or door	no

Materials

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

Dimensions

Insertion depth	72 mm
Depth of wall niche	72 mm
Depth of installed product	97,5 mm
Internal depth	97,5 mm
Height of installed product	418 mm
Installation height	382 mm
Width of installed product	460 mm
Width in division units	18
Thickness of sidewall material	3 mm
Built-in width	426 mm

Installation, mounting

Suitable for outdoor use	no
--------------------------	----

Accessories included

Mounting plate included	yes
With lock	no

Equipment

Number of units	18
Number of rows	2
Quantity of rails	2
Can be accessorized	yes
Extension possible	yes

Standards

GWT Glow wire test	650 °C
--------------------	--------

Safety

IK protection code against mechanical impacts	IK07
---	------