



Presence det. 360° monobloc KNX/DALI

TCC521E

Architecture

Bus system	KNX
------------	-----

Functions

Constant light control	yes
- Linking several detectors in order to expand the detection area	

Configuration

- Output channel for switching, dimming or calling up scenes	
--	--

Controls and indicators

- with programming button	
---------------------------	--

Connectivity

Bus system radio frequent	no
Bus system LON	no
Bus system Powernet	no
- integrated DALI/DSI output (broadcast) for switching/controlling 24 DALI/DSI electronic ballasts	

Voltage

Operating voltage over bus	21 32 V DC
----------------------------	------------

Electric current

Bus current consumption (data transfer)	12 mA
---	-------

Measurement

Detection Method	presence
------------------	----------

Detection

Detection angle	360 °
Angle of vertical detection	55 °
Detection field Ø, on floor	~ 7 m
Detection field Ø, at desk height	~ 5 m
Frontal detecting distance	7 m
Side detecting distance	8 m

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	PC-ABS
Surface appearance	matt

Dimensions

Dimensions (Ø x H)	78 x 70 mm
Installation opening Ø	60 63 mm
Recommended installation height	2,5 3,5 m
Installation wall thickness	10 28 mm

Lighting control

Brightness measurement range	5 / 1000 Lux
------------------------------	--------------

Installation, mounting

Maximum Mounting Height	4 m
Installation mode	with spring clips for ceiling installation

Connection

Conductor cross-section (flexible)	0,5 1,5 mm ²
Conductor cross-section (rigid)	0,5 1,5 mm ²
- with integral bus coupling unit	
- bus connection via connecting terminal	

Settings

Supported configuration modes	system
Delay time, adjustable	1 mn 1 h
- with potentiometers for setting the response brightness and delay time without dismantling	

Scope of delivery

Bus connection included	yes
-------------------------	-----

Equipment

Number of channels	1
Angle of horizontal detection	360 °

Safety

Halogen free	no
--------------	----

Use conditions

Operating temperature	-10 45 °C
Storage/transport temperature	-20 60 °C
- energy saving by presence and brightness-controlled lighting control	

Identification

Main design line	KNX
------------------	-----