



TXB304

## Flush mounted input device 4 -fold

### Architecture

Bus system	EIB
Fixing mode	flush-mounting

### Functions

Bus module detachable	no
<ul style="list-style-type: none"> <li>- Switching functions, dimming functions, blind control functions, priority functions, scene functions, heating functions and timer functions</li> <li>- ETS additional functions: value transmitter 1 and 2 bytes, 2-channel mode, level switch function</li> </ul>	

### Compatibility

- extension unit for light scene push-button
--

### Controls and indicators

- with programming button and red programming LED
---

### Connectivity

- with 2 independent binary inputs for potential-free contacts
- with 2 freely parameterisable outputs for LED activation

### Voltage

Input voltage	5 V
Operating voltage over bus	21 32 V DC
System supply voltage	30V DC via bus

### Electric current

Number of entry circuits	4
Intensity by input	0,5 mA

#### Length

Max distance to switches	5 mm
--------------------------	------

#### Measurement

Input scanning voltage	per channel 5 V
------------------------	-----------------

#### Materials

Colour	stone grey
Material	plastic

#### Dimensions

Dimensions (LLxwwxhh)	38 x 35 x 12 mm
-----------------------	-----------------

#### Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting
-------------------	--

#### Connection

Conductor cross-section (flexible)	0,75 2,5 mm <sup>2</sup>
Conductor cross-section (rigid)	0,75 2,5 mm <sup>2</sup>
Connection to	Potential free, switch, push button, automation system
<ul style="list-style-type: none"> <li>- with integral bus coupling unit</li> <li>- with pre-assembled cable</li> <li>- bus connection via connecting terminal</li> </ul>	

#### Cable

Cable length extendable to	max. 5 m
----------------------------	----------

#### Settings

Supported configuration modes	system, easy
-------------------------------	--------------

#### Scope of delivery

Bus connection included	yes
-------------------------	-----

#### Use

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

#### Safety

Protection index IP	IP30
Halogen free	no

#### Use conditions

Operating temperature	0 45 °C
Storage/transport temperature	-20 70 °C

Identification

Main design line	KNX
------------------	-----