



Premiere 10A vert twin GPO

WBP2VS

Connectivity

| | |
|-----------------------------|-----|
| With USB charging socket | yes |
| Type of USB port | AA |
| - with 2 USB sockets type A | |

Main electrical features

| | |
|-----------------|-------|
| Nominal voltage | 240 V |
| Frequency | 50 Hz |

Voltage

| | |
|----------------|--------|
| Output voltage | 5 V DC |
|----------------|--------|

Electric current

| | |
|---------------|------|
| Rated current | 10 A |
|---------------|------|

Fuse

| | |
|------|-------------------------------------------------------|
| Fuse | short-circuit and overload proof (electronic fuse) |
|------|-------------------------------------------------------|

Dimensions

| | |
|--------|--------|
| Height | 77 mm |
| Width | 117 mm |

Installation, mounting

| | |
|-------------------|----------------------------|
| Screws properties | terminal screws backed off |
| Mounting type | flush-mounted |
| Installation mode | for screw fastening |

Scope of delivery

| | |
|-------------------|-------------------------------------------------------------|
| Scope of delivery | supplied with standard tapered point 32 mm fixing screws |
|-------------------|-------------------------------------------------------------|

Equipment

| | |
|-------------------------------------|---|
| Number of socket outlets switchable | 2 |
|-------------------------------------|---|

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|-------------------------------|--|
| - with overheating protection | |
|-------------------------------|--|

Identification

| | |
|------------------|----------|
| Main design line | premiere |
|------------------|----------|