



Sm.distr, golf, flush, 18M, wh door DZA

VF118PT

#### Architecture

|             |                |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

#### Functions

|                     |     |
|---------------------|-----|
| With a pipe-in lead | yes |
|---------------------|-----|

#### Compatibility

|                                   |     |
|-----------------------------------|-----|
| Compatible with DIN rail mounting | yes |
|-----------------------------------|-----|

#### Main electrical features

|                 |       |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

#### Electric current

|               |      |
|---------------|------|
| Rated current | 80 A |
|---------------|------|

#### Cover, door

|                                    |                |
|------------------------------------|----------------|
| Type of door closing               | Latch          |
| Identification od protection index | 40             |
| Interlockable                      | no             |
| Cover type                         | Closed (plain) |
| Door locking                       | without        |
| Door leave                         | single         |
| Door quantity                      | 1              |
| Cover type                         | Door           |
| Transparent cover or door          | no             |

#### Materials

|                           |                       |
|---------------------------|-----------------------|
| Colour                    | pure white            |
| Colour                    | white                 |
| RAL colour                | RAL 9010 - Pure white |
| Material                  | plastic               |
| Type of surface treatment | untreated             |

#### Dimensions

|                             |         |
|-----------------------------|---------|
| Insertion depth             | 72 mm   |
| Depth of wall niche         | 72 mm   |
| Depth of installed product  | 97,5 mm |
| Internal depth              | 97,5 mm |
| Height of installed product | 293 mm  |
| Installation height         | 257 mm  |
| Width of installed product  | 460 mm  |
| Width in division units     | 18      |
| Built-in height             | 257 mm  |
| Built-in width              | 426 mm  |

#### Installation, mounting

|                          |    |
|--------------------------|----|
| Suitable for outdoor use | no |
|--------------------------|----|

#### Accessories included

|                         |    |
|-------------------------|----|
| Mounting plate included | no |
| With lock               | no |

#### Equipment

|                              |     |
|------------------------------|-----|
| Number of rows               | 1   |
| Quantity of section in width | 1   |
| Quantity of rails            | 1   |
| Can be accessorized          | yes |
| Extension possible           | yes |

#### Standards

|                    |        |
|--------------------|--------|
| GWT Glow wire test | 850 °C |
|--------------------|--------|

#### Safety

|                                               |               |
|-----------------------------------------------|---------------|
| IK protection code against mechanical impacts | 07            |
| Protection index IP                           | IP40          |
| Protection class                              | isol.class II |
| Halogen free                                  | yes           |
| Ultraviolet resistant                         | no            |

#### Use conditions

|                       |           |
|-----------------------|-----------|
| Operating temperature | -25 40 °C |
|-----------------------|-----------|