



Sm.distr, golf, flush, 36M, white door DZA

VF218PT

**Architecture**

Fixing mode	flush-mounting
-------------	----------------

**Functions**

With a pipe-in lead	yes
---------------------	-----

**Compatibility**

Compatible with DIN rail mounting	yes
-----------------------------------	-----

**Main electrical features**

Nominal voltage	400 V
-----------------	-------

**Electric current**

Rated current	80 A
---------------	------

**Cover, door**

Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	Closed (plain)
Door locking	without
Door leave	single
Door quantity	1
Cover type	Door
Transparent cover or door	no

**Materials**

Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material	plastic
Type of surface treatment	untreated

**Dimensions**

Insertion depth	72 mm
Depth of wall niche	72 mm
Depth of installed product	97,5 mm
Internal depth	97,5 mm
Height of installed product	418 mm
Installation height	382 mm
Width of installed product	460 mm
Width in division units	18
Built-in height	382 mm
Built-in width	426 mm

**Installation, mounting**

Suitable for outdoor use	no
--------------------------	----

**Accessories included**

Mounting plate included	no
With lock	no

**Equipment**

Number of rows	2
Quantity of section in width	1
Quantity of rails	2
Can be accessorized	yes
Extension possible	yes

**Standards**

GWT Glow wire test	850 °C
--------------------	--------

**Safety**

IK protection code against mechanical impacts	07
Protection index IP	IP40
Protection class	isol.class II
Halogen free	yes
Ultraviolet resistant	no

**Use conditions**

Operating temperature	-25 40 °C
-----------------------	-----------