



Similar image
(Picture shows JPE2400S25DS)

DB, elite, 60/30P, Split, 160A ISO-DIN-SS

Architecture

| | |
|------------------------------------|------------------|
| Fixing mode | surface-mounting |
| Number of poles of the main switch | 3 |

Functions

| | |
|------------------------|----|
| Overvoltage protection | no |
|------------------------|----|

Main electrical features

| | |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

Electric current

| | |
|---------------|-------|
| Rated current | 160 A |
|---------------|-------|

Cover, door

| | |
|---------------------------|---------------|
| Type of door closing | 3-point lever |
| Interlockable | no |
| Transparent cover or door | no |

Materials

| | |
|----------|-----------------|
| Material | stainless steel |
|----------|-----------------|

Dimensions

| | |
|--------------------------------|---------|
| Insertion depth | 250 mm |
| Depth of installed product | 250 mm |
| Internal depth | 248 mm |
| Height of installed product | 1600 mm |
| Width of installed product | 600 mm |
| Thickness of sidewall material | 1,2 mm |

Connection

| | |
|-----------------------------|----|
| Number of accessible phases | 90 |
|-----------------------------|----|

Accessories included

| | |
|-------------------------|-----|
| Mounting plate included | no |
| With lock | yes |

Equipment

| | |
|-----------------------|-----|
| Quantity of rails | 3 |
| Can be accessorized | no |
| With bell transformer | no |
| Extension possible | yes |

Safety

| | |
|---|--------------|
| IK protection code against mechanical impacts | 05 |
| Protection index IP | IP66 |
| Protection class | isol.class I |