



## 4P 40A Centre Off Changeover , Top

SFT440

### Architecture

Type of order	Changeover switch
Number of poles	4 P
Type of pole	4 P

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	400 V

### Voltage

Rated insulation voltage	440 V
Type of voltage input 1	AC
Rated impulse withstand voltage	4000 V

### Electric current

Rated operational current in AC21 category A	40 A
Rated operational current in AC21 category B	40 A
Acceptable current rating with AC22 category A	40 A
Acceptable current rating with AC22 category B	40 A
Short-circuit current with gI-gG fuses	600 A
Closing ability with 400V in AC23A	846 A
Rated short-circuit making capacity Icm under 415V AC according IEC 60947-3	480 A
Rated short-time withstand current 1s	0,6 kA
Thermal rated current outside of housings	40 A

### Power

Power loss per pole at In	2,1 W
Total power loss under IN	8,4 W

### Endurance

Electrical durability at nominal load in AC21 in operating cycles	25000
Electrical durability at nominal load in AC22 in operating cycles	25000
Number of mechanical operations	200000

#### Dimensions

Depth of installed product	71 mm
Height of installed product	83 mm
Width of installed product	70 mm

#### Installation, mounting

Tightening torque	1,8Nm
-------------------	-------

#### Connection

Cage clamp position	off set
Connection cross-sect. rigid cable	1,5 / 16mm <sup>2</sup>
Connection cross-sect. flexible conductor	1,5 / 10mm <sup>2</sup>
Type of connection	with screw

#### Equipment

Quantity of INV contacts	4
--------------------------	---

#### Standards

Standard text	IEC 60947-3
European directive WEEE	concerned

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Degree of pollution according to IEC 60664 / IEC 60947-2	2
Altitude	2000 m
Storage temperature	-40 to 80 °C

#### Identification

Device family	SFT
---------------	-----