



Power supply 30V DC 320 mA

TXA111

Architecture

Bus system	EIB
Fixing mode	Din-Rail

Connectivity

Bus lines	max. 1
- one output 30 V DC, 320 mA incl. choke	

Main electrical features

Frequency	50/60 Hz
-----------	----------

Voltage

Output voltage	28 - 32 V
Output voltage	30V DC
Filtered output voltage	30V +/- 2V

Electric current

Output intensity	320 mA
Output current	max. 320 mA

Fuse

- with electronic short-circuit and overload protection

Power

Total power loss under IN	15 W
---------------------------	------

Materials

RAL colour	RAL 7035 - Light grey
Colour	stone grey

Dimensions

Depth of installed product	64 mm
Height of installed product	90 mm
Length	64 mm
Width of installed product	72 mm
Width of rail mounted device (RMD)	4 modules

LED control

- with green LED for display of power supply
- with red LED for display of short-circuit and overload protection per output

Connection

Conductor cross-section (flexible)	0,75 2,5 mm ²
Conductor cross-section (rigid)	0,75 2,5 mm ²
Connection cross-sect. rigid cable	0,75 / 2.5mm ²
Connection cross-sect. flexible conductor	0,75 / 2,5mm ²
Type of connection	quick connect

- protected earth conductor must be connected
- with QuickConnect plug-in terminals

Equipment

Power failure bypass	yes
----------------------	-----

Use

- with labelling field

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5 45 °C
Storage temperature	-20 to 70 °C